



SPECIFICATIONS	
LUMENS	100
MAX WATTAGE	2.4
NO. OF LEDs	1
I @ 12V	0.1
I @ 24V	0.1
BEAM ANGLE	90 Deg FWHM
LIGHT DIA	44mm (1.73")
LIGHT HEAD HEIGHT	10mm (0.04")
LIGHT OVERALL LENGTH	20.3mm (0.8")
MOUNT HOLE PCD	17mm (0.67")
HULL CUTOFF DIA	30mm (1.18")
LIGHT APERTURE	10mm (.79")
WEIGHT	30gm
LENS	OPAL 050 ACRYLIC

CABLE LENGTH SHOWN FOR REPRESENTATION ONLY. REFER TO SPECIFICATION FOR ACTUAL SUPPLIED LENGTH

DETAIL B SCALE 4 : 1
LIGHT ENGINE SCREWS INTO BEZEL ASSEMBLY

THIRD ANGLE PROJECTION
Sheet. 1 of 3
Scale. 2:1
A3

Iss	Rev	Status	Date	Change	Drawn	Chk'd	App'vd
04	A	DEV	02/01/2017		DWL	DWL	

ALL DIMENSIONS ARE IN MILLIMETERS
 TOLERANCES ON CASTINGS, UNMACHINED PARTS AND FABRICATIONS, +/- 0.8
 TOLERANCES ON MACHINED DIMENSIONS
 WHOLE UNITS +/- 0.25
 ONE DEC. PLACE +/- 0.1
 TWO DEC. PLACE +/- 0.05
 ANGLES +/- 0.5 DEG.
 ALL UNSPECIFIED CHAMFERS 1 x 45
 BREAK ALL SHARP EDGES 0.1 TO 0.5

Notes.
 P1 COURTESY LIGHT AVAILABLE IN:
 WARM WHITE
 COOL WHITE
 BLUE
 GREEN
 RED

Description.	P1 SIDE EMITTING COURTESY LIGHT		
Material.			
Finish.			
DWG No.	Iss.	Rev.	Status.
GAE-0133 Iss 04A	04	A	DEVELOPMENT

© 2014 COASTLINE LED THIS DOCUMENT MUST NOT BE REPRODUCED IN WHOLE OR IN PART AND MUST NOT BE USED OR DISCLOSED WITHOUT THE WRITTEN AUTHORISATION OF COASTLINE LED. NO DEVIATION FROM THIS DRAWING IS PERMISSABLE WITHOUT WRITTEN AUTHORISATION FROM COASTLINE LED.